Test method catalogue



Test method (price range for one run in €)	Standar d	
Tensile test (60 to 350) on Test specimen, Films, Parts in standard climate 23 / 50, at temperatures from -80°C to 250°C Thermoplastics Films Elastomers	ISO 527-1 / -2 ISO 527-1 / -3 ISO 37	*
3-Point Flexural test (60 to 350) on Test specimen, Parts in standard climate 23 / 50, at temperatures from -80°C to 250°C Thermoplastics Fibre-reinforced plastic composites	ISO 178 ISO 14125	*
Creep- or Relaxation Test in Tensile or Flexural mode (from 300) on Test specimen, Films, Parts in standard climate 23 / 50, at temperatures from -80°C to 250°C Thermoplastics	ISO 899-1 / -2	
Compression test (60 to 350) on Test specimen, Parts in standard climate 23 / 50, at temperatures from -80°C to 250°C Thermoplastics	ISO 604	
Impact test (60 to 120) on Test specimen, Parts in standard climate 23 / 50, at temperatures from -80°C to 130°C Thermoplastics, acc. Charpy Thermoplastics, acc. Izod	ISO 179-1 ISO 180	*
Tensile Impact test (60 to 120) on Test specimen, Films, Parts in standard climate 23 / 50, at temperatures from -80°C to 130°C Thermoplastics	ISO 8256	
Instrumented puncture test (100 to 300) on Test specimen, Films, Parts in standard climate 23 / 50, at temperatures from -80°C to 130°C Thermoplastics Films	ISO 6603-2 ISO 7765-2	
Hardness (60 to 120) on Test specimen, Parts Ball Indentation hardness Shore Hardness, Method A and D	ISO 2039-1 ISO 868	*
Density (60 to 120) on Test specimen, Parts Method A – Immersion method	ISO 1183-1	*
Test specimen preparation (60 to 120) Mechanical preparation of specimen from parts (cutting, notching) Conditioning of test specimen, parts at special climate	ISO 2818 ISO 62, ISO 1110	**

www.polymerphysik.de



Test method (price range for one run in €)	Standar d	
Vicat Softening temperature (60 to 120) on Test specimen, Parts at temperatures up to 300°C Thermoplastics	ISO 306	*
Temperature of deflection under load in oil (60 to 120) on Test specimen, Parts at temperatures up to 300°C Thermoplastics	ISO 75-1 / -2	*
Mineral-filler content, Ash content (60 to 120) on Granules, Test specimen, Parts at temperatures up to 1100°C Textile-glass-reinforced plastics, Calcination method A Plastics, determination of ash	ISO 1172 ISO 3451-1	*
Fogging behaviour (100 to 300) on Test specimen, Parts Method A (Reflection) and Method B (condensable constituent)	DIN 75 201	
Heat Aging (from 50 one day) on Test specimen, Parts Aging ovens for ageing procedures Determination of thermal oxidative stability in air	IEC 60216-4-1 ISO 4577	**
Melt flow rate MFR & MVR (100 to 300) on Granules, Test specimen, Parts Procedure A (mass measurement) and B (distance measurement)	ISO 1133-1 / -2	
Measurement of parts by picture analysis (200 to 500) e. G. statistical distribution of fibre length	ISO 22314	
FTIR-Analysis (150 to 300) Transmission, Microscope: Transmission, Reflection, ATR Organic compounds, IR-Spectroscopy Petroleum products and related products, IR Analysis	DIN EN 6042 DIN 51451	

With our modern laboratory equipment, further test possibilities exist. Ask us. Demand us.

The price range serves an orientation and is not obligatory.

We generate you gladly a tailor-made offer, on the basis of your te

We generate you gladly a tailor-made offer, on the basis of your test inquiry.

Test method catalogue Nr. 12, published 25.05.2013 Replaces all test method catalogues with older publishing date Responsible: Management board of polymerphys IK GmbH

Copyright

The content of this test method catalogue is protected by copyright.

The duplication, distribution, utilization or public reproduction of the test method catalogue and its content is allowed only with specific approval of the polymerphys IK GmbH. A shortened or in excerpts reproduction, duplication or the translation of the test method catalogue, indifferently for which purposes, is generally not allowed.

www.polymerphysik.de

^{*} standardized test method in the scope of accreditation acc. DIN EN ISO/IEC 17025:2005

^{**} test method referenced by the scope of accreditation